



**EIT1 MÓDULO RECTO 1 M**  
**STRAIGHT PIPE 1 M**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	950	950	950	950	950	950	950	950	945	945	945	945	945	945	945	945	945	945
A	35	35	35	35	35	35	35	35	50	50	50	50	50	50	50	50	50	50


**EITO MÓDULO RECTO 0,5 M**  
**STRAIGHT PIPE 0,5 M**

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	445	445	445	445	445	445	445	445	445	445


**MÓDULO RECTOS 0,25 M**
**EITP STRAIGHT PIPE 0,25 M**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	200	200	200	200	200	200	200	200	195	195	195	195	195	195	195	195	195	195


**EITG TE 90° DE 1 M CON SALIDA Ø80 MM**  
**TEE 90° WITH Ø80 MM CONNECTION**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	950	950	950	950	950	950	950	-	-	-	-	-	-	-	-	-	-
B	-	800	800	800	800	800	800	800	-	-	-	-	-	-	-	-	-	-


**EITE MÓDULO EXTENSIBLE 0,25 A 0,40 M**  
**ADJUSTABLE PIPE 0,25 TO 0,40 M**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L min	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250
L max	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400


**EIEL MÓDULO EXTENSIBLE 0,80 A 1,30 M**  
**ADJUSTABLE PIPE 0,80 TO 1,30 M**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L min	800	800	800	800	800	800	800	800	-	-	-	-	-	-	-	-	-	-
L max	1300	1300	1300	1300	1300	1300	1300	1300	-	-	-	-	-	-	-	-	-	-


**EIMC MÓDULO DE COMPROBACIÓN 0,5 M**  
**CHECKING PIPE 0,5 M**

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	445	445	445	445	445	445	445	445	445	445


**EIRN CODO 90° CON REGISTRO**  
**INSPECTION ELBOW 90°**

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	115	125	138	149	161	173	197	220	-	-	-	-	-	-	-	-	-	-
Y	94	104	135	147	160	172	197	222	-	-	-	-	-	-	-	-	-	-



**EITU MÓDULO DE INSPECCIÓN 0,5 M**  
**INSPECTION PIPE 0,5 M**

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	-	-	-	-	-	-	-	-	-	-


**EITI TE DE INSPECCIÓN**  
**INSPECTION TEE**

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	200	220	245	270	305	330	400	450	-	-	-	-	-	-	-	-	-	-


**EITJ TE DE 0,5M REGISTRO Ø100**


**Ø100 INSPECTION TEE 0,5M**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	-	-	-	-	-	-	-	-	-	-
B	225	225	225	225	225	225	225	225	-	-	-	-	-	-	-	-	-	-

**EICR MÓDULO CON COMPUERTA DE REGULACIÓN DE TIRO**  
**PIPE 0,5 M WITH MANUAL DAMPER**



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	450	450	-	-	-	-	-	-	-	-

**EIET ESTABILIZADOR DE TIRO**  
**DRAUGHT STABILISER**



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	108	108	108	150	150	150	150	150	-	-	-	-	-	-	-	-	-	-
C	175	90	175	90	175	185	140	140	-	-	-	-	-	-	-	-	-	-

**EICQ CODO 15°**  
**ELBOW 15°**



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	16	16	15	16	16	16	17	18	24	25	26	27	28	28	29	30	31	32
Y	97	99	105	108	111	114	121	127	183	187	196	202	209	215	222	228	235	241

**EICT CODO 30°**  
**ELBOW 30°**



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	33	34	33	35	37	38	42	45	59	62	65	69	72	75	79	82	85	89
Y	101	106	115	121	127	134	146	159	218	231	243	255	268	281	293	306	318	331

**EICC CODO 45°**  
**ELBOW 45°**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	51	54	54	57	61	65	72	79	101	108	116	123	130	138	145	170	159	167
Y	101	108	120	126	138	146	164	182	244	261	279	297	314	332	350	360	385	403

**EICH CODO 87°**  
**ELBOW 87°**



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	115	125	138	149	161	173	197	220	270	294	318	342	390	389	413	436	460	484
Y	94	104	135	147	160	172	197	222	285	310	335	360	361	410	435	460	485	510

**EICN CODO 90°**  
**ELBOW 90°**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	115	125	138	149	161	173	197	220	270	294	318	342	390	389	413	436	460	484
Y	94	104	135	147	160	172	197	222	285	310	335	360	361	410	435	460	485	510


**EITN TE 90°**  
**TEE 90°**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	170	195	245	270	305	330	400	450	495	535	585	635	685	735	785	845	945	945
B	118	128	123	135	153	165	200	225	260	285	310	335	360	385	410	444	489	494
C	77	87	108	120	133	145	170	195	225	250	275	300	325	350	375	400	425	450


**EITW TE 90° CON INJERTO HEMBRA**  
**TEE 90° WITH FEMALE CONNECTION**


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	170	195	245	270	305	330	400	450	-	-	-	-	-	-	-	-	-	-
B	118	128	123	135	153	165	200	225	-	-	-	-	-	-	-	-	-	-
C	60	60	70	70	70	70	70	70	-	-	-	-	-	-	-	-	-	-


**EITB TE 87°**


**TEE 87°**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	170	195	245	270	305	330	400	450	-	-	-	-	-	-	-	-	-	-
B	118	130	123	135	153	165	200	225	-	-	-	-	-	-	-	-	-	-
C	102	112	128	140	153	165	190	215	-	-	-	-	-	-	-	-	-	-

**EITC TE 135°**
**TEE 135°**



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	218	246	277	312	348	383	450	524	630	701	771	935	935	984	1054	1125	1196	1267
B	170	191	214	241	267	294	345	400	506	559	612	665	718	771	824	877	930	983
C	98	115	139	160	181	203	245	288	348	391	434	476	519	562	604	647	690	732

**EITS TE 135° ESTANCA**
**TEE 135° TIGHT**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	218	246	277	312	348	383	450	524	630	701	771	935	935	984	1054	1125	1196	1267
B	170	191	214	241	267	294	345	400	506	559	612	665	718	771	824	877	930	983
C	98	115	139	160	181	203	245	288	348	391	434	476	519	562	604	647	690	732

**EITA TAPA SIN DRENAJE**
**LID WITHOUT DRAIN**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	33	33	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60


**TAPA CON DRENAJE**
**LID WITH DRAIN**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	48	48	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75


**TAPA CON DRENAJE HORIZONTAL**
**LID WITH HORIZONTAL DRAIN**

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	33	33	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60


**EICP CAPERUZA**
**CAP**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	135	140	160	185	205	230	275	315	-	-	-	-	-	-	-	-	-	-
C	160	210	250	300	350	400	500	580	-	-	-	-	-	-	-	-	-	-


**EICA CAPERUZA ANTIRREVOCO**
**ANTI-WIND COWL**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	175	175	195	195	195	205	215	220	-	-	-	-	-	-	-	-	-	-
C	230	250	275	300	325	430	480	530	-	-	-	-	-	-	-	-	-	-


**EICD CAPERUZA ANTIVIENTO**
**ANTI-WIND TOP TERMINAL**



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	220	223	235	239	250	260	292	314	-	-	-	-	-	-	-	-	-	-
C	160	210	252	302	350	400	500	595	-	-	-	-	-	-	-	-	-	-

**EITH** TERMINAL SALIDA HORIZONTAL  
 HORIZONTAL END



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	100	115	135	150	170	185	220	255	310	345	380	415	465	500	535	570	605	640

**EICF** TERMINAL DE FACHADA  
 WALL END



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	140	160	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
C	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

**EICO** CONO DE SALIDA LIBRE  
 CONE

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	105	115	135	160	185	210	235	285	355	355	355	355	355	355	355	355	355	355

**EIAA** AUTO-ASPIRADOR  
 ROTATING COWL



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	-	-	235	265	290	300	370	420	-	-	-	-	-	-	-	-	-	-
C	-	-	195	225	260	280	350	420	-	-	-	-	-	-	-	-	-	-

**EIMM** MANGUITO DE UNIÓN MACHO-MACHO  
 COUPLING MALE-MALE



∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	50	50	55	55	55	55	55	55	-	-	-	-	-	-	-	-	-	-

**MANGUITO DE UNIÓN HEMBRE-HEMBRA**
**EIHH** COUPLING FEMALE-FEMALE


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	100	100	100	100	100	100	100	100	-	-	-	-	-	-	-	-	-	-

**EIUB** MANGUITO UNIVERSAL A BI  
 ADAPTOR SINGLE WALL TO BI


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	110	110	110	110	110	110	110	110	-	-	-	-	-	-	-	-	-	-

**EISU** MANGUITO UNIVERSAL A BI CON PLACA  
 ADAPTOR SINGLE WALL TO BI WITH PLATE


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	316	316	316	316	316	316	316	316	-	-	-	-	-	-	-	-	-	-
C	250	250	250	250	250	250	250	250	-	-	-	-	-	-	-	-	-	-
D	162	182	207	232	257	282	332	382	-	-	-	-	-	-	-	-	-	-

**EIAM** AMPLIACIÓN  
 INCREASER


∅A	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
∅B	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800	-
L útil	175	175	175	175	175	175	175	175	195	195	195	195	195	195	195	195	195	-


**EIRE** REDUCCIÓN  
 REDUCTION

∅A	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
∅B	-	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750


L útil	-	175	175	175	175	175	175	175	175	195	195	195	195	195	195	195	195	195	195
--------	---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB.C.	100+130	120+150	145+175	170+200	195+225	220+250	270+300	320+350	370+400	420+450	470+500	520+550	570+600	620+650	670+700	720+750	770+800	820+850
L útil	175	175	175	175	175	175	175	175	-	-	-	-	-	-	-	-	-	-


B	40	40	40	40	40	40	40	40	40	-	-	-	-	-	-	-	-	-
---	----	----	----	----	----	----	----	----	----	---	---	---	---	---	---	---	---	---


**EISB SOPORTE BASE REGULABLE**  
**ADJUSTABLE BASE SUPPORT**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	-	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
B	-	-	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80


**EISP SOPORTE PLACA**  
**CONSOLATE PLATE**


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	100	100	100	100	100	100	100	100	135	135	135	135	135	135	135	135	135	135
B	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80


**EIAD ADAPTADOR A CALDERA +0 A +15-TIPO 1**  
**BOILER ADAPTOR +0 TO +15-TYPE 1**

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
∅B.C.	80+95	100+115	125+140	150+165	175+190	200+215	250+265	300+315	350+365	400+415	450+465	500+515	550+565	600+615	650+665	700+715	750+765	800+815
L útil	95	95	90	90	90	90	90	90	-	-	-	-	-	-	-	-	-	-


**EIAD ADAPTADOR A CALDERA -50 A -5-TIPO 2**  
**BOILER ADAPTOR -50 TO -5-TYPE 2**

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
∅B.C.	30+75	50+95	75+120	100+145	125+170	150+195	200+245	250+295	300+345	350+395	400+445	450+495	500+545	550+595	600+645	650+695	700+745	750+795
L útil	-	140	140	140	140	140	140	140	-	-	-	-	-	-	-	-	-	-


**EIAD ADAPTADOR A CALDERA +20 A +50-TIPO 3**  
**BOILER ADAPTOR +20 TO +50-TYPE 3**
