


BIT1 **MÓDULO 1 m**
PIPE 1 m

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	950	950	950	950	950	950	950	950	945	945	945	945	945	945	945	945	945	945
A	35	35	35	35	35	35	35	35	50	50	50	50	50	50	50	50	50	50


BIT0 **MÓDULO 0,5 m**
PIPE 0,5 m


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	445	445	445	445	445	445	445	445	445	445


BITP **MÓDULO 0,25 m**
PIPE 0,25 m

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	200	200	200	200	200	200	200	200	195	195	195	195	195	195	195	195	195	195


BITE **MÓDULO EXTENSIBLE 0,25 A 0,40 m**
ADJUSTABLE PIPE 0,25 TO 0,40 m


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L min	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250
L max	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400


BIEL **MÓDULO EXTENSIBLE 0,80 A 1,30 m**
ADJUSTABLE PIPE 0,80 TO 1,30 m


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L min	800	800	800	800	800	800	800	800	-	-	-	-	-	-	-	-	-	-
L max	1300	1300	1300	1300	1300	1300	1300	1300	-	-	-	-	-	-	-	-	-	-


BICQ **CODO 15°**
ELBOW 15°


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	16	16	15	16	16	16	17	18	25	26	27	28	29	30	31	31	32	33
Y	102	104	105	108	111	114	121	127	183	187	196	202	209	215	222	228	235	241


BICT **CODO 30°**
ELBOW 30°


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	33	34	33	35	37	38	42	45	61	64	68	71	74	78	81	84	88	91
Y	106	111	115	121	127	134	146	159	218	230	243	254	268	280	293	305	318	330


BICC **CODO 45°**
ELBOW 45°


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	51	54	54	55	61	65	72	79	104	112	119	126	134	141	148	156	163	170
Y	106	113	120	127	138	146	164	182	242	260	277	295	313	331	348	366	384	401


BICH **CODO 87°**
ELBOW 87°


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	110	120	139	151	163	174	198	222	277	301	325	348	372	396	420	443	467	491
Y	99	109	137	149	162	173	199	224	282	307	332	357	382	407	432	457	482	507


BICN **CODO 90°**
ELBOW 90°


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	114	121	144	156	169	181	206	231	288	313	338	363	388	413	438	463	488	513
Y	97	104	134	146	159	171	196	221	273	298	323	348	373	398	423	448	473	498


BITG TE 90° DE 1 m CON SALIDA Ø80 mm
 TEE 90° 1 m WITH Ø80 mm CONNECTION


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	950	950	950	950	950	950	950	-	-	-	-	-	-	-	-	-	-
B	-	800	800	800	800	800	800	800	-	-	-	-	-	-	-	-	-	-


BITN TE 90°
 TEE 90°

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	171	191	245	283	305	330	400	450	535	535	585	635	685	735	785	845	944	944
B	118	128	123	142	153	165	200	225	260	285	310	335	360	385	410	444	489	494
C	77	87	108	120	133	145	170	195	225	250	275	300	325	350	375	400	425	450


BITW TE 90° CON INJERTO HEMBRA
 TEE 90° FEMALE CONNECTION


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	171	191	245	283	305	330	400	450	-	-	-	-	-	-	-	-	-	-
B	112	128	123	142	153	165	200	225	-	-	-	-	-	-	-	-	-	-
C	100	110	133	146	158	171	196	221	-	-	-	-	-	-	-	-	-	-


BITB TE 93°
 TEE 93°

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	171	191	245	283	305	330	400	450	535	535	585	635	685	735	785	845	944	944
B	118	128	123	142	153	165	200	225	260	285	310	335	360	385	410	444	489	494
C	82	92	108	120	133	145	170	195	225	250	275	300	325	350	375	400	425	450


BITC TE 135°
 TEE 135°

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	218	246	277	312	348	383	450	524	630	700	771	935	935	984	1054	1125	1196	1267
B	170	191	214	241	267	294	345	400	506	559	612	665	718	771	824	877	930	983
C	98	115	139	160	181	203	245	288	348	391	434	476	519	562	604	647	690	732


BITS TE 135° ESTANCA
 TEE 135° TIGHTNESS


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	218	246	277	312	348	383	450	524	630	700	771	935	935	984	1054	1125	1196	1267
B	170	191	214	241	267	294	345	400	506	559	612	665	718	771	824	877	930	983
C	98	115	139	160	181	203	245	288	348	391	434	476	519	562	604	647	690	732


BITA TAPA
 LID

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	33	33	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60


BITD TAPA CON DRENAJE
 LID WITH DRAIN

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	48	48	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75


BITF TAPA CON DRENAJE HORIZONTAL
 LID WITH HORIZONTAL DRAIN


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	83	83	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80


BITY TAPA LARGA
 LONG LID


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	70	70	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-


BITZ TAPA CON DRENAJE LARGA
LONG LID WITH DRAIN


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	90	90	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-


BITL TE 90° LARGA
LONG TEE 90°


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	198	223	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B	112	128	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
C	78	89	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-


BITK TE 90° LARGA INJERTO HEMBRA
LONG TEE 90° FEMALE

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	198	223	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B	112	128	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
C	100	110	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-


BIMC MÓDULO DE COMPROBACIÓN 0,5 m
TESTING PIPE 0,5 m


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	445	445	445	445	445	445	445	445	445	445


BIRN CODO 90° CON REGISTRO
INSPECTION ELBOW 90°


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
X	-	-	144	156	169	181	206	231	-	-	-	-	-	-	-	-	-	-
Y	-	-	134	146	159	171	196	221	-	-	-	-	-	-	-	-	-	-


BITU MÓDULO DE INSPECCIÓN 0,5 m
INSPECTION PIPE 0,5 m


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	-	450	450	450	450	450	450	-	-	-	-	-	-	-	-	-	-


BITI TE DE INSPECCIÓN
INSPECTION TEE

∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	200	220	245	283	305	330	400	450	495	535	585	635	685	735	785	845	945	945


BITJ TE DE 0,5 m REGISTRO Ø100
Ø100 INSPECTION TEE 0,5 m


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	-	450	450	450	450	450	450	445	445	445	445	445	445	445	445	445	445
B	-	-	225	225	225	225	225	225	225	225	225	225	225	225	225	225	225	225


BICR COMPUERTA DE REGULACIÓN DE TIRO 0,5 m
PIPE 0,5 m WITH MANUAL DAMPER


∅	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	-	-	450	450	450	450	450	450	445	445	-	-	-	-	-	-	-	-


BIDA COMPUERTA 0,5 m CON TIRADOR
HANDLE DAMPER 0,5 m


∅int	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	450	450	450	450	450	450	450	450	-	-	-	-	-	-	-	-	-	-
A	100	100	100	100	100	100	100	100	-	-	-	-	-	-	-	-	-	-


BIET ESTABILIZADOR DE TIRO
 DRAUGHT STABILISER


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	108	108	108	150	150	150	150	150	-	-	-	-	-	-	-	-	-	-
C	175	90	175	90	175	185	140	140	-	-	-	-	-	-	-	-	-	-


BICP CAPERUZA
 CAP


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	118	140	160	180	200	222	280	330	-	-	-	-	-	-	-	-	-	-
C	160	200	250	300	350	400	500	600	-	-	-	-	-	-	-	-	-	-


BICA CAPERUZA ANTIRREVOCO
 ANTI-WIND COWL

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	140	140	160	160	160	170	180	185	-	-	-	-	-	-	-	-	-	-
C	200	200	250	300	350	400	450	500	-	-	-	-	-	-	-	-	-	-


BICD CAPERUZA ANTIVIENTO
 ANTI-WIND TOP TERMINAL

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	182	182	202	204	204	216	250	268	-	-	-	-	-	-	-	-	-	-
C	200	250	250	300	350	400	500	600	-	-	-	-	-	-	-	-	-	-


HIMC MALLA PARA CAPERUZA ANTIVIENTO
 MESH FOR ANTI-WIND TOP TERMINAL

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	120	120	135	135	135	145	155	165	-	-	-	-	-	-	-	-	-	-
ØB	137	157	181	207	232	257	307	357	-	-	-	-	-	-	-	-	-	-


BICO CONO DE SALIDA LIBRE
 CONE


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	105	115	135	160	185	210	235	285	355	355	355	355	355	355	355	355	355	355


BICG CAPERUZA GIRATORIA
 ROTATING CAP

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	145	145	148	148	148	170	152	152	-	-	-	-	-	-	-	-	-	-
C	200	200	250	250	250	315	400	400	-	-	-	-	-	-	-	-	-	-


BIAA AUTO-ASPIRADOR
 ROTATING COWL

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	-	-	400	400	400	400	480	480	-	-	-	-	-	-	-	-	-	-
C	-	-	270	270	270	270	380	380	-	-	-	-	-	-	-	-	-	-


BITH TERMINAL SALIDA HORIZONTAL
 HORIZONTAL END


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	100	115	135	150	170	185	220	255	-	-	-	-	-	-	-	-	-	-


BICF TERMINAL DE FACHADA
 WALL END


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	140	160	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
C	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

BIMM MANGUITO DE UNIÓN MACHO-MACHO
 COUPLING MALE-MALE



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	50	50	55	55	55	55	55	55	-	-	-	-	-	-	-	-	-	-

BIHH MANGUITO DE UNIÓN HEMBRA-HEMBRA
 COUPLING FEMALE-FEMALE


Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	80	80	80	80	80	80	80	80	-	-	-	-	-	-	-	-	-	-

BIAM AMPLIACIÓN
 INCREASER



ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800	-
L útil	175	175	175	175	175	175	175	175	195	195	195	195	195	195	195	195	195	-

BIAM AMPLIACIÓN 2 DIÁMETROS
 INCREASER 2 DIAMETERS



ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800	-	-
L útil	175	175	175	175	212	250	250	275	275	275	275	275	275	275	275	275	-	-

BIAM AMPLIACIÓN 3 DIÁMETROS
 INCREASER 3 DIAMETERS



ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800	-	-	-
L útil	205	212	212	250	287	325	325	325	345	345	345	345	345	345	345	-	-	-

BIRE REDUCCIÓN
 REDUCER



ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	-	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750
L útil	-	175	175	175	175	175	175	175	195	195	195	195	195	195	195	195	195	195

BIRE REDUCCIÓN 2 DIÁMETROS
 REDUCER 2 DIAMETERS



ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	-	-	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700
L útil	-	-	175	175	175	175	212	250	250	275	275	275	275	275	275	275	275	275

BIRE REDUCCIÓN 3 DIÁMETROS
 REDUCER 3 DIAMETERS


ØA	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB	-	-	-	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650
L útil	-	-	-	205	212	212	250	287	325	325	325	345	345	345	345	345	345	345

BISB SOPORTE BASE REGULABLE 50 A 80 mm
 ADJUSTABLE BASE SUPPORT 50 TO 80 mm



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
B	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80	50-80

BISP SOPORTE PLACA
 CONSULATE PLATE



Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L útil	100	100	100	100	100	100	100	100	135	135	135	135	135	135	135	135	135	135
B	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80


HISB
SOPORTE BASE REGULABLE 0 A 120 mm
ADJUSTABLE BASE SUPPORT 0 TO 120 mm


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
L	-	-	154	130	167	184	187	200	214	-	-	-	-	-	-	-	-	-
J	-	-	170	195	220	245	295	345	395	-	-	-	-	-	-	-	-	-
B	-	-	0-120	0-120	0-120	0-120	0-120	0-120	0-120	-	-	-	-	-	-	-	-	-


HISA
SOPORTE MURAL REGULABLE 50 A 80 mm
ADJUSTABLE WALL SUPPORT 50 TO 80 mm


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Amin.	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50
Amax.	80	80	80	80	80	80	80	80	80	50	50	50	50	50	50	50	50	50
B	30	30	30	30	40	40	40	40	40	40	40	40	40	60	60	60	60	60


HIS1
SOPORTE MURAL REGULABLE 80 A 130 mm
ADJUSTABLE WALL SUPPORT 80 TO 130 mm


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Amin.	80	80	80	80	80	80	80	80	80	80	80	80	80	80	-	-	-	-
Amax.	130	130	130	130	130	130	130	130	130	130	130	130	130	130	-	-	-	-
B	30	30	30	30	40	40	40	40	40	40	40	40	40	60	-	-	-	-


HIS2
SOPORTE MURAL REGULABLE 130 A 210 mm
ADJUSTABLE WALL SUPPORT 130 TO 210 mm


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Amin.	130	130	130	130	130	130	130	130	130	130	130	130	130	130	-	-	-	-
Amax.	210	210	210	210	210	210	210	210	210	210	210	210	210	210	-	-	-	-
B	30	30	30	30	40	40	40	40	40	40	40	40	40	60	-	-	-	-


HIS4
SOPORTE MURAL REGULABLE 80 A 440 mm
ADJUSTABLE WALL SUPPORT 80 TO 440 mm


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Amin.	80	80	80	80	80	80	80	80	80	-	-	-	-	-	-	-	-	-
Amax.	440	440	440	440	440	440	440	440	440	-	-	-	-	-	-	-	-	-
B	30	30	30	30	40	40	40	40	40	-	-	-	-	-	-	-	-	-


HIS5
SOPORTE MURAL DE ESQUINA
CORNER WALL SUPPORT

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Amin.	270	270	270	270	270	270	270	270	270	-	-	-	-	-	-	-	-	-
Amax.	520	520	520	520	520	520	520	520	520	-	-	-	-	-	-	-	-	-
B	30	30	30	30	40	40	40	40	40	-	-	-	-	-	-	-	-	-


HISF
SOPORTE FORJADO
JOIST SUPPORT

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150
B	30	30	30	30	40	40	40	40	40	40	40	40	40	60	60	60	60	60


HIST
SOPORTE DE TEJADO
ROOF SUPPORT

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	150	150	150	150	150	150	150	150	150	-	-	-	-	-	-	-	-	-
B	30	30	30	30	40	40	40	40	40	-	-	-	-	-	-	-	-	-


HISV
SOPORTE DE TEJADO REFORZADO
REINFORCED ROOF SUPPORT


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	-	-	250	250	250	250	250	250	250	-	-	-	-	-	-	-	-	-
B	-	-	80	80	80	80	80	80	80	-	-	-	-	-	-	-	-	-
C	-	-	150	150	150	150	150	150	150	-	-	-	-	-	-	-	-	-


HISS
SOPORTE SUELO
FLOOR SUPPORT


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	65	75	88	100	113	125	-	-	-	-	-	-	-	-	-	-	-	-
B	30	30	30	30	40	40	-	-	-	-	-	-	-	-	-	-	-	-
Hmin.	80	80	80	80	80	80	-	-	-	-	-	-	-	-	-	-	-	-
Hmax.	300	300	300	300	300	300	-	-	-	-	-	-	-	-	-	-	-	-


HISH
SOPORTE MONTAJE HORIZONTAL INOX.
HORIZONTAL SUPPORT INOX.


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	30	30	30	30	40	40	40	40	40	40	40	40	40	60	60	60	60	60


HIPE
PLACA EMBELLECEDORA DE 0-30°
INOX. FINISHING PLATE 0-30°


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	83	103	128	153	178	203	253	303	353	403	453	503	553	603	-	-	-	-
B	263	283	308	333	415	440	490	540	590	640	690	740	790	840	-	-	-	-
C	90	90	90	90	90	90	90	90	90	90	90	90	90	90	-	-	-	-


HIPB
PLACA EMBELLECEDORA DE 30-45°
INOX. FINISHING PLATE 30-45°


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	83	103	128	153	178	203	253	303	353	403	453	503	553	603	-	-	-	-
B	263	283	308	333	415	440	490	540	590	640	690	740	790	840	-	-	-	-
C	90	90	90	90	90	90	90	90	90	90	90	90	90	90	-	-	-	-


HIPS
PLACA EMBELLECEDORA REDONDA DE 90°
INOX. ROUND FINISHING PLATE 90°


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	85	105	130	155	180	205	255	305	355	-	-	-	-	-	-	-	-	-
B	233	253	278	303	328	353	403	453	503	-	-	-	-	-	-	-	-	-
C	74	74	74	74	74	74	74	74	74	-	-	-	-	-	-	-	-	-
D	127	137	149	162	174	187	212	237	262	-	-	-	-	-	-	-	-	-


HIPT
PLACA EMBELLECEDORA REDONDA DE 45°
INOX. ROUND FINISHING PLATE 45°

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	85	105	130	155	180	205	255	305	355	-	-	-	-	-	-	-	-	-
B	233	253	278	303	328	353	403	453	503	-	-	-	-	-	-	-	-	-
C	74	74	74	74	74	74	74	74	74	-	-	-	-	-	-	-	-	-
D	144	158	176	193	211	229	264	299	335	-	-	-	-	-	-	-	-	-


HIPU
PLACA EMBELLECEDORA REDONDA 150 - 90°
INOX. ROUND FINISHING PLATE WIDE 150 - 90°

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	85	105	130	155	180	205	255	305	355	-	-	-	-	-	-	-	-	-
B	383	403	428	453	478	503	553	603	653	-	-	-	-	-	-	-	-	-
C	150	150	150	150	150	150	150	150	150	-	-	-	-	-	-	-	-	-
D	202	212	224	237	249	262	287	312	337	-	-	-	-	-	-	-	-	-


HIPW
PLACA EMBELLECEDORA REDONDA 150 - 45°
INOX. ROUND FINISHING PLATE WIDE 150 - 45°


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	85	105	130	155	180	205	255	305	355	-	-	-	-	-	-	-	-	-
B	383	403	428	453	478	503	553	603	653	-	-	-	-	-	-	-	-	-
C	150	150	150	150	150	150	150	150	150	-	-	-	-	-	-	-	-	-
D	219	233	251	268	286	304	339	374	410	-	-	-	-	-	-	-	-	-


HITJ **TAPAJUNTAS**
WALL ROSETTE


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	30	30	40	40	40	40	50	50	50	70	70	70	100	100	100	100	100	100
B	15	15	15	15	15	15	15	15	15	25	25	25	25	25	25	25	25	25


HIPM **PASAMUROS**
INOX. WALL SLEEVE


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØA	100	125	150	175	200	225	300	350	400	450	500	550	600	650	-	-	-	-
B	325	325	325	325	325	325	325	325	325	325	325	325	325	325	-	-	-	-


HICU **CUBREAGUAS ALUMINIO 0-35° + COLLARÍN ANTILLUVIA**
ALUMINIUM FLASHING 0-35° + STORM COLLAR

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	132	140	150	160	170	180	200	220	250	270	290	310	-	-	-	-	-	-
C	105	125	150	175	200	225	275	325	375	425	475	525	-	-	-	-	-	-
D	171	194	229	257	294	321	376	431	503	561	620	680	-	-	-	-	-	-


HICW **CUBREAGUAS GOMA 0-20°**
RUBBER FLASHING 0-20°

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	624	645	671	697	723,5	750	813	865	917	-	-	-	-	-	-	-	-	-
B	605	625	650	675	700	700	775	800	800	-	-	-	-	-	-	-	-	-
C	90	110	135	160	185	210	270	320	370	-	-	-	-	-	-	-	-	-


HICX **CUBREAGUAS GOMA 20-45°**
RUBBER FLASHING 20-45°

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
A	689	717	751	786	820	840	1000	1000	1000	-	-	-	-	-	-	-	-	-
B	605	625	650	675	700	700	775	800	800	-	-	-	-	-	-	-	-	-
C	90	110	135	160	185	210	270	320	370	-	-	-	-	-	-	-	-	-


HILL **COLLARÍN ANTILLUVIA**
STORM COLLAR


ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Øext	130	150	200	225	275	300	350	400	450	525	575	625	675	725	-	-	-	-
Øint	80	100	125	150	175	200	250	300	350	400	450	500	550	600	-	-	-	-
A	50	50	75	75	100	100	100	100	100	125	125	125	125	125	-	-	-	-


HILM **COLLARÍN ANTILLUVIA CORTO**
SHORT STORM COLLAR

ØNom	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Øext	204	226	251	276	302	326	376	426	476	-	-	-	-	-	-	-	-	-
Øint	79	100	126	151	176	201	251	301	351	-	-	-	-	-	-	-	-	-
A	32	32	32	32	32	32	32	32	32	-	-	-	-	-	-	-	-	-


KWSD **MANGUITO DE UNIÓN BI A KW**
ADAPTOR BI TO KW

Øint	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Lútil	134	134	134	134	134	134	134	134	-	-	-	-	-	-	-	-	-	-


KWDS **MANGUITO DE UNIÓN KW A BI**
ADAPTOR KW TO BI

Øint	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Lútil	140	140	140	140	140	140	140	140	-	-	-	-	-	-	-	-	-	-


BIBV MANGUITO DE UNIÓN BI A VB
ADAPTOR BI TO VB

ØVB	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Lútil	60	60	60	60	60	60	60	-	-	-	-	-	-	-	-	-	-	-


BIVB MANGUITO DE UNIÓN VB A BI
ADAPTOR VB TO BI

ØVB	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
Lútil	50	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-


IFBIF MANGUITO DE UNIÓN BI A FLEX
ADAPTOR BI TO FLEX


Øflex	80	100	125	150	180	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	155	155	155	155	155	155	155	155	-	-	-	-	-	-	-	-	-	-


IFFBI MANGUITO DE UNIÓN FLEX A BI
ADAPTOR FLEX TO BI


Øflex	80	100	125	150	180	200	250	300	350	400	450	500	550	600	650	700	750	800
ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
B	150	150	150	150	150	150	150	150	-	-	-	-	-	-	-	-	-	-


BIUB MANGUITO UNIVERSAL A BI
ADAPTOR SINGLE WALL TO BI


ØBI	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØA	78	98	123	148	173	198	248	298	348	398	448	498	548	598	648	698	748	798
B	70	70	90	90	90	90	90	90	-	-	-	-	-	-	-	-	-	-


BIAD ADAPTADOR A CALDERA +0 A +15-TIPO 1
BOILER ADAPTOR +0 TO +15-TYPE 1

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB.C.	80÷95	100÷115	125÷140	150÷165	175÷190	200÷215	250÷265	300÷315	350÷365	400÷415	450÷465	500÷515	550÷565	600÷615	650÷665	700÷715	750÷765	800÷815
Lútil	95	95	90	90	90	90	90	90	-	-	-	-	-	-	-	-	-	-


BIAD ADAPTADOR A CALDERA -50 A -5-TIPO 2
BOILER ADAPTOR -50 TO -5-TYPE 2

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB.C.	30÷75	50÷95	75÷120	100÷145	125÷170	150÷195	200÷245	250÷295	300÷345	350÷395	400÷445	450÷495	500÷545	550÷595	600÷645	650÷695	700÷745	750÷795
Lútil	-	180	180	180	180	180	180	180	-	-	-	-	-	-	-	-	-	-


BIAD ADAPTADOR A CALDERA +20 A +50-TIPO 3
BOILER ADAPTOR +20 TO +50-TYPE 3

Ø	80	100	125	150	175	200	250	300	350	400	450	500	550	600	650	700	750	800
ØB.C.	100÷130	120÷150	145÷175	170÷200	195÷225	220÷250	270÷300	320÷350	370÷400	420÷450	470÷500	520÷550	570÷600	620÷650	670÷700	720÷750	770÷800	820÷850
Lútil	175	175	175	175	175	175	175	175	-	-	-	-	-	-	-	-	-	-
B	40	40	40	40	40	40	40	40	-	-	-	-	-	-	-	-	-	-