

KCT1 MÓDULO 1 m
PIPE 1 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	950	950	950	950	950	950	950	950
A	40	40	40	40	40	40	40	40


KCT0 MÓDULO 0,5 m
PIPE 0,5 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	450	450	450	450	450


KCTP MÓDULO 0,25 m
PIPE 0,25 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	200	200	200	200	200	200	200	200


KCEP MÓDULO EXTENSIBLE 0,25 A 0,35 m
ADJUSTABLE PIPE 0,25 TO 0,35 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lmin	250	250	250	250	250	250	250	250
Lmax	350	350	350	350	350	350	350	350


KCEG MÓDULO EXTENSIBLE 0,35 A 0,5 m
ADJUSTABLE PIPE 0,35 TO 0,5 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lmin	350	350	350	350	350	350	350	350
Lmax	500	500	500	500	500	500	500	500


KCE5 MÓDULO EXTENSIBLE 0,5 A 0,82 m
ADJUSTABLE PIPE 0,5 TO 0,82 m

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lmin	500	500	500	500	500	500	500	500
Lmax	820	820	820	820	820	820	820	820



KCMS MÓDULO SILENCIADOR 1 m
SILENCER PIPE 1 m

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	950	950	950	950	950	950	950	950




**KCCQ CODO 15°
ELBOW 15°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
X	17	18	19	20	20	21	22	23
Y	171	177	183	190	192	203	209	216




**KCCT CODO 30°
ELBOW 30°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
X	47	50	54	57	60	64	67	70
Y	215	227	240	252	262	277	290	302




**KCCC CODO 45°
ELBOW 45°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
X	84	94	102	109	116	124	131	138
Y	243	268	285	303	321	338	356	374




**KCCH CODO 87°
ELBOW 87°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
X	273	297	321	345	-	-	-	-
Y	332	357	382	407	-	-	-	-




**KCCN CODO 90°
ELBOW 90°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
X	286	311	336	361	-	-	-	-
Y	330	355	380	405	-	-	-	-




**KCTN TE 90°
TEE 90°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
Lútil	536	586	636	686	736	786	836	886
B	246	271	296	321	346	371	396	421
C	290	315	340	365	390	415	440	465



**KCTB TE 93°
TEE 93°**

∅int	350	400	450	500	550	600	650	700
∅ext	400	450	500	550	600	650	700	750
Lútil	536	586	636	686	736	786	836	886
B	251	276	301	326	351	376	401	426
C	300	327	353	379	404	432	458	484


KCTC **TE 135°**
TEE 135°

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	723	793	942	942	1006	1076	1147	1218
B	552	605	659	711	764	818	870	923
C	412	455	498	540	583	626	668	711


KCTA **TAPA**
LID

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	49	49	49	49	49	49	49	49


KCTD **TAPA CON DRENAJE**
LID WITH DRAIN

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	60	60	60	60	60	60	60	60


KCTF **TAPA CON DRENAJE HORIZONTAL**
LID WITH HORIZONTAL DRAIN


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	49	49	49	49	49	49	49	49


KCMC **MÓDULO COMPROBACIÓN 0,5 m**
INSPECTION LENGHT 0,5 m

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	450	450	450	450	450


KCTS **TE 90° 0,5 m CON REGISTRO Ø100**
TEE 90° 0,5 m WITH Ø100 INSPECTION DOOR


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	450	450	450	450	450


KCTU **MÓDULO 0,5 m CON REGISTRO**
INSPECTION DOOR 0,5 m


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	450	450	450	450	450


KCTR **MÓDULO 0,5 m CON REGISTRO E130**
INSPECTION DOOR 0,5 m E130


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	450	450	450	450	450
B	245	245	245	245	245	245	245	245
Ød	220	220	220	220	220	220	220	220


KCTQ MÓDULO 1 m CON REGISTRO EI30
INSPECTION DOOR 1 m EI30

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	950	950	950	950	950	950	950	950
B	495	495	495	495	495	495	495	495
Ød	220	220	220	220	220	220	220	220


KCTI TE DE INSPECCIÓN
INSPECTION TEE


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	536	586	636	686	736	786	836	886
B	246	271	296	321	346	371	396	421
C	339	364	389	414	439	464	489	514


KCRN CODO 90° CON REGISTRO
ELBOW 90° INSPECTION


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
X	264	289	314	339	-	-	-	-
Y	304	329	354	379	-	-	-	-


KCCR COMPUERTA 0,5 m REGULACIÓN DE TIRO
MANUAL DAMPER 0,5 m

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	450	450	450	-	-	-	-	-
B	207	207	207	-	-	-	-	-


KCCP CAPERUZA
RAIN CAP


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	453	488	509	517	524	532	539	547
C	750	840	900	950	1000	1050	1100	1150


KCCA CAPERUZA ANTIRREVOCO
ANTI WIND COWL


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	385	395	450	460	470	520	530	540
C	750	800	900	950	1000	1150	1200	1250


KCCO CONO SALIDA
CONE


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	250	250	250	250	250	250	250	250


KCJE CAPERUZA JET
JET CAP

Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
B	815	907	995	1082	1170	1257	-	-
C	621	700	779	858	936	1015	-	-


KCTH **TERMINAL HORIZONTAL CON REJILLA**
HORIZONTAL END WITH MESH


\varnothing_{int}	350	400	450	500	550	600	650	700
\varnothing_{ext}	400	450	500	550	600	650	700	750
B	430	465	490	535	570	605	640	675


KCMM **MANGUITO MACHO - MACHO**
COUPLING MALE - MALE


\varnothing_{int}	350	400	450	500	550	600	650	700
\varnothing_{ext}	400	450	500	550	600	650	700	750
Lútil	50	50	50	50	50	50	50	50


KCHH **MANGUITO HEMBRA - HEMBRA**
COUPLING FEMALE - FEMALE


\varnothing_{int}	350	400	450	500	550	600	650	700
\varnothing_{ext}	400	450	500	550	600	650	700	750
Lútil	120	120	120	120	120	120	120	120


KCAM **AMPLIACIÓN**
INCREASER


\varnothing_{Aint}	350	400	450	500	550	600	650	-
\varnothing_{Bint}	400	450	500	550	600	650	700	-
Lútil	205	205	205	205	205	205	205	-


KCAM **AMPLIACIÓN 2 DIÁMETROS**
INCREASER 2 DIAMETERS


\varnothing_{Aint}	350	400	450	500	550	600	-	-
\varnothing_{Bint}	450	500	550	600	650	700	-	-
Lútil	280	280	280	280	280	280	-	-


KCAM **AMPLIACIÓN 3 DIÁMETROS**
INCREASER 3 DIAMETERS


\varnothing_{Aint}	350	400	450	500	550	-	-	-
\varnothing_{Bint}	500	550	600	650	700	-	-	-
Lútil	355	355	355	355	355	-	-	-


KCRE **REDUCCIÓN**
REDUCER


\varnothing_{Aint}	400	450	500	550	600	650	700	-
\varnothing_{Bint}	350	400	450	500	550	600	650	-
Lútil	205	205	205	205	205	205	205	-


KCAM **REDUCCIÓN 2 DIÁMETROS**
REDUCER 2 DIAMETERS


\varnothing_{Aint}	450	500	550	600	650	700	-	-
\varnothing_{Bint}	350	400	450	500	550	600	-	-
Lútil	280	280	280	280	280	280	-	-


KCAM **REDUCCIÓN 3 DIÁMETROS**
REDUCER 3 DIAMETERS

ØAint	500	550	600	650	700	-	-	-
ØBint	350	400	450	500	550	-	-	-
Lútil	355	355	355	355	355	-	-	-


KCSB **SOPORTE BASE REGULABLE 50 A 80 mm**
ADJUSTABLE BASE SUPPORT 50 TO 80 mm


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	250	250	250	250	250	250	250	250
Bmin	50	50	50	50	50	50	50	50
Bmax	80	80	80	80	80	80	80	80


KCSR **SOPORTE BASE REGULABLE 80 A 280 mm**
ADJUSTABLE BASE SUPPORT 80 TO 280 mm


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	250	250	250	250	250	250	250	250
Bmin	80	80	80	80	80	80	80	80
Bmax	280	280	280	280	280	280	280	280


KCSP **PLACA DE SOPORTE BASE**
CONSOLE PLATE


Øint	350	400	450	500	550	600	650	700
Øext	400	450	500	550	600	650	700	750
Lútil	142	142	142	142	142	142	142	142
B	100	100	100	100	100	100	100	100


HISA **SOPORTE MURAL REGULABLE 50 A 80 mm**
INOX. WALL SUPPORT ADJUSTABLE 50 TO 80 mm


Øext	400	450	500	550	600	650	700	750
Amin	50	50	50	50	50	50	50	50
Amax	80	80	80	80	80	80	80	80
B	40	40	40	40	60	60	60	60


HIS1 **SOPORTE MURAL REGULABLE 80 A 130 mm**
INOX. WALL SUPPORT ADJUSTABLE 80 TO 130 mm


Øext	400	450	500	550	600	650	700	750
Amin	80	80	80	80	80	80	-	-
Amax	130	130	130	130	130	130	-	-
B	40	40	40	40	60	60	-	-


HIS2 **SOPORTE MURAL REGULABLE 130 A 210 mm**
INOX. WALL SUPPORT ADJUSTABLE 130 TO 210 mm


Øext	400	450	500	550	600	650	700	750
Amin	130	130	130	130	130	130	-	-
Amax	210	210	210	210	210	210	-	-
B	40	40	40	40	60	60	-	-


HISF **SOPORTE FORJADO**
JOIST SUPPORT


\varnothing_{ext}	400	450	500	550	600	650	700	750
A	150	150	150	150	150	150	150	150
B	40	40	40	40	60	60	60	60


HISH **SOPORTE MONTAJE HORIZONTAL INOX.**
HORIZONTAL SUPPORT


\varnothing_{ext}	400	450	500	550	600	650	700	750
B	40	40	40	40	60	60	60	60


HIAV **ABRAZADERA DE VIENTOS**
ANTI-WIND LOCKING BAND

\varnothing_{ext}	400	450	500	550	600	650	700	750
B	40	40	40	40	60	60	60	60


HIPM **PASAMUROS INOX.**
INOX. WALL SLEEVE


\varnothing_{ext}	400	450	500	550	600	650	700	750
$\varnothing A$	450	500	550	600	650	700	750	800
B	325	325	325	325	325	325	325	325


HICU **CUBREAGUAS ALUMINIO 0 A 35° + COLLARÍN ANTILLUVIA**
ALUMINIUM FLASHING 0 TO 35° + STORM COLLAR


\varnothing_{ext}	400	450	500	550	600	650	700	750
B	270	290	310	-	-	-	-	-
C	425	475	525	-	-	-	-	-
D	561	620	680	-	-	-	-	-


HILL **COLLARÍN ANTILLUVIA**
STORM COLLAR


\varnothing_{ext}	400	450	500	550	600	650	700	750
\varnothing_{ext}	525	575	625	675	725	800	850	900
\varnothing_{int}	400	450	500	550	600	650	700	750
A	125	125	125	125	125	150	150	150


KCSDM **ADAPTADOR A CALDERA MACHO**
MALE BOILER ADAPTOR


\varnothing_{int}	350	400	450	500	550	600	650	700
B.C	350	400	450	500	550	600	650	700
Lútil	170	170	170	170	170	170	170	170


KCSAM **ADAPTADOR A CALDERA MACHO AMPLIADO**
INCREASER MALE BOILER ADAPTOR


\varnothing_{int}	350	400	450	500	550	600	650	700
B.C	300	350	400	450	500	550	600	650
Lútil	170	170	170	170	170	170	170	170


KCAD ADAPTADOR A CALDERA HEMBRA TIPO 1
FEMALE BOILER ADAPTOR TYPE 1


Øint	350	400	450	500	550	600	650	700
B.C	350÷365	400÷415	450÷465	500÷515	550÷565	600÷615	650÷675	700÷715
Lútil	170	170	170	170	170	170	170	170


KCAD ADAPTADOR A CALDERA HEMBRA TIPO 2
FEMALE BOILER ADAPTOR TYPE 2

Øint	350	400	450	500	550	600	650	700
B.C	330÷345	380÷395	430÷445	480÷495	530÷545	580÷595	630÷645	680÷695
Lútil	245	245	245	245	245	245	245	245


KCAD ADAPTADOR A CALDERA HEMBRA TIPO 3
FEMALE BOILER ADAPTOR TYPE 3

Øint	350	400	450	500	550	600	650	700
B.C	370÷395	420÷445	470÷495	520÷545	570÷595	620÷645	670÷695	720÷745
Lútil	220	220	220	220	220	220	220	220

DESVIACIÓN / DEVIATION


CODO	L	Ø350/400		Ø400/450		Ø450/500		Ø500/550		Ø550/600		Ø600/650		Ø650/700		Ø700/750	
		X	Y	X	Y	X	Y	X	Y	X	Y	X	Y	X	Y	X	Y
45°	-	196	474	217	524	231	559	246	594	261	630	275	665	290	700	305	736
	0,25 m	338	616	358	665	373	700	388	736	402	771	417	806	432	842	446	877
	0,5 m	515	857	535	842	550	877	564	913	579	948	594	983	608	1019	623	1054
	1 m	868	1146	889	1196	903	1230	918	1266	933	1302	947	1336	962	1372	977	1408
30°	-	114	425	120	449	127	475	134	499	139	519	147	549	154	575	160	599
	0,25 m	214	598	220	622	227	648	234	672	239	692	247	722	254	748	260	772
	0,5 m	339	814	345	838	352	865	359	888	364	909	372	939	379	964	385	988
	1 m	589	1247	595	1271	602	1298	609	1321	614	1342	622	1372	629	1397	635	1421
15°	-	44,8	341	46,4	353	48	365	49,9	379	50,4	383	53,3	405	54,8	417	56,7	431
	0,25 m	96,6	534	98,2	546	99,8	558	102	572	102	576	105	598	107	610	108	624
	0,5 m	161	775	163	787	164	799	166	813	167	817	170	839	171	851	173	865
	1 m	291	1258	292	1270	294	1282	296	1296	296	1300	299	1322	301	1334	303	1348