

**VBT1** MÓDULO 1 m  
**PIPE 1 m**


Ø	80	100	125	150	175	200	250
L útil	960	960	945	945	945	945	945
A	40	40	55	55	55	55	55


**VBT0** MÓDULO 0,5 m  
**PIPE 0,5 m**


Ø	80	100	125	150	175	200	250
L útil	460	460	445	445	445	445	445


**VBTP** MÓDULO 0,25 m  
**PIPE 0,25 m**


Ø	80	100	125	150	175	200	250
L útil	210	210	195	195	195	195	195


**VBTE** MODULO EXTENSIBLE 0,10 A 0,25 m  
**ADJUSTABLE PIPE 0,10 TO 0,25 m**


Ø	80	100	125	150	175	200	250
L max.	245	245	245	245	245	245	245
L min.	100	100	100	100	100	100	100


**VBDA** REGULADOR DE TIRO CON TIRADOR 0,5 m  
**MANUAL DAMPER WITH HANDLE 0,5 m**


Ø	80	100	125	150	175	200	-
L útil	460	460	445	445	445	445	-
A	100	100	100	100	100	100	-


**VBRT** REGULADOR DE TIRO  
**PIPE WITH MANUAL DAMPER**


Ø	80	100	125	150	175	200	250
L útil	210	210	445	445	445	445	445
B	125	125	250	250	250	250	250


**VBCC** CODO 45°  
**ELBOW 45°**


Ø	80	100	125	150	175	200	250
X	58	61	71	75	79	82	88
Y	99	106	116	126	135	144	158


**VBCN** CODO 90°  
**ELBOW 90°**

Ø	80	100	125	150	175	200	250
X	134	142	167	179	190	204	229
Y	94	102	112	124	135	149	174




<b>VB TN</b>		<b>TE 90°</b>						
		<b>TEE 90°</b>						
$\emptyset$		80	100	125	150	175	200	250
L útil		150	170	210	235	260	285	335
B		95	105	133	145	158	170	195
C		60	70	83	95	108	120	145




<b>VB TW</b>		<b>TE 90° SALIDA CALDERA HEMBRA</b>						
		<b>TEE 90° FEMALE CONEXION</b>						
$\emptyset$		80	100	125	150	175	200	250
L útil		150	170	210	235	260	285	335
B		95	105	133	145	158	170	195
C		100	110	118	130	143	155	145




<b>VB TA</b>		<b>TAPA</b>						
		<b>LID</b>						
$\emptyset$		80	100	125	150	175	200	250
B		50	47	60	50	60	60	60



<b>VB TK</b>		<b>TE 90° CORTA SALIDA CALDERA HEMBRA CON TAPA</b>						
		<b>TEE 90° SHORT FEMALE CONEXION WITH LID</b>						
$\emptyset$		80	100	-	-	-	-	-
L útil		165	185	-	-	-	-	-
B		95	105	-	-	-	-	-
C		102	112	-	-	-	-	-




<b>VB TL</b>		<b>TE 90° CORTA CON TAPA</b>						
		<b>TEE 90° SHORT WITH LID</b>						
$\emptyset$		80	100	-	-	-	-	-
L útil		165	185	-	-	-	-	-
B		95	105	-	-	-	-	-
C		48	72	-	-	-	-	-




<b>VB R1</b>		<b>MÓDULO 1 m CON REGISTRO</b>						
		<b>INSPECTION PIPE 1 m</b>						
$\emptyset$		80	100	125	150	175	200	250
L útil		960	960	945	945	945	945	945
B		45	60	90	100	130	130	160




<b>VB R0</b>		<b>MÓDULO 0,5 m CON REGISTRO</b>						
		<b>INSPECTION PIPE 0,5 m</b>						
$\emptyset$		80	100	125	150	175	200	250
L útil		460	460	445	445	445	445	445
B		45	60	90	100	130	130	160




<b>VB RP</b>		<b>MÓDULO 0,25 m CON REGISTRO</b>						
		<b>INSPECTION PIPE 0,25 m</b>						
$\emptyset$		80	100	125	150	-	-	-
L útil		460	460	445	445	-	-	-
B		45	60	90	100	-	-	-


**VBRC**      **CODO 45° CON REGISTRO**  
**INSPECTION ELBOW 45°**


∅	80	100	125	150	175	200	250
B	45	60	90	100	130	130	160
X	58	61	71	75	79	82	88
Y	144	161	192	201	230	229	261


**VBRN**      **CODO 90° CON REGISTRO**  
**INSPECTION ELBOW 90°**

∅	80	100	125	150	175	200	250
B	45	60	90	100	130	130	160
X	134	142	167	179	190	204	229
Y	94	102	112	124	135	149	174


**VBCP**      **CAPERUZA**  
**CAP**

∅	80	100	125	150	175	200	250
L útil	128	130	144	162	191	214	241
B	160	200	250	300	350	400	400


**VBCA**      **CAPERUZA ANTIRREVOCO**  
**ANTI WIND COWL**

∅	80	100	125	150	175	200	-
B	150	145	175	175	175	205	-
C	200	200	250	300	375	375	-


**VBTH**      **TERMINAL HORIZONTAL**  
**HORIZONTAL END**


∅	80	100	125	150	175	200	-
L útil	85	99	118	135	153	170	-


**VBMM**      **MANGUITO MACHO-MACHO**  
**ADAPTOR MALE-MALE**


∅	80	100	125	150	175	200	250
B	100	100	125	125	125	125	125


**VBHH**      **MANGUITO HEMBRA-HEMBRA**  
**ADAPTOR FEMALE-FEMALE**

∅	80	100	125	150	175	200	250
B	100	100	125	125	125	125	125


**VBAM**      **AMPLIACIÓN**  
**INCREASER**


∅A	80	100	125	150	175	200	-
∅B	100	125	150	175	200	250	-
L útil	160	160	145	145	145	170	-


**VBAM AMPLIACIÓN 2 DIÁMETROS**  
**INCREASER 2 DIAMETERS**

ØA	80	100	125	150	-	-	-
ØB	125	150	175	200	-	-	-
L útil	160	160	145	145	-	-	-


**VBAM AMPLIACIÓN 3 DIÁMETROS**  
**INCREASER 3 DIAMETERS**


ØA	80	100	125	-	-	-	-
ØB	150	175	200	-	-	-	-
L útil	160	160	145	-	-	-	-


**VBRE REDUCCIÓN**  
**REDUCER**


ØA	-	100	125	150	175	200	250
ØB	-	80	100	125	150	175	200
L útil	-	160	160	145	145	145	170


**VBTJ TAPAJUNTAS**  
**WALL ROSETTE**


Ø	80	100	125	150	175	200	250
B	130	150	190	215	240	265	312


**VBSE SOPORTE MURAL DE UN ENCLAVAMIENTO**  
**WALL SUPPORT 1 SCREW**


Ø	80	100	125	150	175	200	250
B	12	12	12	12	12	12	12


**VBSA SOPORTE MURAL REGULABLE 50 A 80 mm**  
**ADJUSTABLE WALL SUPPORT 50 TO 80 mm**


Ø	80	100	125	150	175	200	250
Bmin	50	50	50	50	50	50	50
Bmax	80	80	80	80	80	80	80


**VBTI TUBO DE INICIO ANTIGOTEO 1 m**  
**STARTING PIPE ANTICONDENSING 1 m**


Ø	-	-	125	150	175	200	250
L útil	-	-	1000	1000	1000	1000	1000
ØC	-	-	110	135	160	185	235
ØD	-	-	128	153	178	203	253


**VBAG ADAPTADOR A CALDERA ANTIGOTEO**  
**ANTICONDENSING BOILER ADAPTOR**


Ø	-	100	125	150	175	200	250
L útil	-	140	140	140	140	140	140
ØC	-	85	110	135	160	185	234
ØD	-	103	128	153	178	203	253


**VBAP** PROLONGADOR A CALDERA 0,25 m PARA TE 90° SALIDA HEMBRA CON JUNTA  
 PROLONGATION TEE 90° FEMALE CONEXION TO BOILER 0,25 m WITH SEAL

Ø	80	100	-	-	-	-	-
B.C	80	100	-	-	-	-	-
L útil	200	200	-	-	-	-	-


**VBAQ** PROLONGADOR A CALDERA 0,25 m PARA TE 90° CON JUNTA  
 PROLONGATION TEE 90° TO BOILER 0,25 m WITH SEAL


Ø	80	100	-	-	-	-	-
B.C	80	100	-	-	-	-	-
L útil	250	250	-	-	-	-	-


**VBAD** ADAPTADOR A CALDERA TIPO 1  
 BOILER ADAPTOR TYPE 1


Ø	80	100	125	150	175	200	-
B.C	80+90	100+110	125+130	150	175+180	200	-
L	100	100	125	125	125	125	-
B	40	40	40	40	40	40	-


**VBAD** ADAPTADOR A CALDERA TIPO 2  
 BOILER ADAPTOR TYPE 2


Ø	-	100	125	150	175	200	-
B.C	-	80	100+120	125+140	150+160	150+180	-
L	-	160	180	180	180	180	-
B	-	55	55	55	55	55	-


**VBAD** ADAPTADOR A CALDERA TIPO 3  
 BOILER ADAPTOR TYPE 3


Ø	80	100	125	150	175	200	-
B.C	100	125	150	175	200	250	-
L	160	160	205	205	205	205	-
B	55	55	55	55	55	55	-


**VBADxxl** ADAPTADOR A CALDERA HEMBRA CON JUNTA  
 FEMALE BOILER ADAPTOR WITH SEAL


Ø	80	100	-	-	-	-	-
B.C	80	100	-	-	-	-	-
L	100	100	-	-	-	-	-


**VBAD** ADAPTADOR A CALDERA MACHO  
 MALE BOILER ADAPTOR


Ø	80	-	-	-	-	-	-
B.C	78	-	-	-	-	-	-
L	100	-	-	-	-	-	-


**KWVD** MANGUITO (VB) A (KW)  
 ADAPTER (VB) TO (KW)


Øint	80	100	-	-	-	-	-
ØVB	80	100	-	-	-	-	-
L útil	100	100	-	-	-	-	-


**KWDV**      **MANGUITO (KW) A (VB)**  
**COUPLING (KW) TO (VB)**

∅int	80	100	125	150	175	200	250
∅VB	80	100	125	150	175	200	250
L útil	170	170	170	170	170	170	170


**BIVB**      **MANGUITO DE UNIÓN (VB) A (BI)**  
**ADAPTOR (VB) TO (BI)**

∅VB	80	100	125	150	175	200	250
∅BI	80	100	125	150	175	200	250
Lútil	50	50	-	-	-	-	-


**BIBV**      **MANGUITO DE UNIÓN (BI) A (VB)**  
**ADAPTOR (BI) TO (VB)**

∅VB	80	100	125	150	175	200	250
∅BI	80	100	125	150	175	200	250
Lútil	60	60	60	60	60	60	60