


BIT1 MÓDULO RECTO 1 m
STRAIGHT PIPE 1 m


Øint	150	175	200	250	300
Lútil	950	950	950	950	950
A	35	35	35	35	35


SET1 MÓDULO RECTO 1 m CON CANALIZACIÓN
STRAIGHT PIPE 1 m WITH CANAL


Øint	150	175	200	250	300
Lútil	950	950	950	950	950
A	35	35	35	35	35


SEEL MÓDULO EXTENSIBLE 0,80 A 1,30 m CON CANALIZACIÓN
ADJUSTABLE PIPE 0,80 TO 1,30 m WITH CANAL


Øint	150	175	200	250	300
Lmin	800	800	800	800	800
Lmax	1300	1300	1300	1300	1300


SETG TE 90° 1 m CON CANALIZACIÓN
TEE 90° 1 m WITH CANAL


Øint	150	175	200	250	300
Lútil	950	950	950	950	950
B	125	125	125	125	125


BITA TAPA
LID


Øint	150	175	200	250	300
B	60	60	60	60	60


HISB SOPORTE BASE REGULABLE 0 A 120 mm
BASE SUPPORT 0 TO 120 mm


Øext	150	175	200	250	300
L	160	167	174	187	200
J	199	224	249	299	349
B	0-120	0-120	0-120	0-120	0-120


BICP CAPERUZA
CAP


Øint	150	175	200	250	300
B	180	200	222	280	330
C	300	350	400	500	600


HISA SOPORTE MURAL REGULABLE 50 A 80 mm
ADJUSTABLE WALL SUPPORT 50 TO 80 mm


Øext	150	175	200	250	300
Amin	50	50	50	50	50
Amax	80	80	80	80	80
B	30	40	40	40	40


HISF **SOPORTE FORJADO**
JOIST SUPPORT

ϕ_{ext}	150	175	200	250	300
A	150	150	150	150	150
B	30	40	40	40	40


HIAV **ABRAZADERA DE VIENTOS**
ANTI-WIND LOCKING BAND

ϕ_{ext}	150	175	200	250	300
B	30	40	40	40	40


HICU **CUBREAGUAS ALUMINIO 0-35° + COLLARÍN ANTILLUVIA**
ALUMINIUM FLASHING 0-35° + STORM COLLAR

ϕ_{ext}	150	175	200	250	300
B	160	170	180	200	220
C	175	200	225	275	325
D	257	294	321	376	431